FORKLIFT

Diesel or Electric or LPG



ALWAYS USE COMMON SENSE

This Equipment Safety Data Sheet is intended as a guide only for the safe operation of this Forklift. It does not override Worksafe NZ recommendations or the manufacturers recommendations or any other industry requirements. You must be a competent qualified person to operate this Forklift. If you are unsure about any aspect of this equipment or its capabilities or its suitability, or if you are in doubt as to its proper usage you must contact one of the Hire Company Employees or an industry expert before continuing.

IMPORTANT HAZARDS



Danger! Collisions between Forklifts and pedestrians can be fatal! You must have a Pedestrian Management Plan to minimise the risk of collisions between forklifts, goods and pedestrians.



Risk of Tipping! Never exceed the load capacity of the Forklift or the maximum slope. Always carry the load in as low a position as possible. Avoid turning with load raised. Always wear your seatbelt!



Risk of crush! Avoid travelling with fork blades higher than 150mm above ground. Load must be at lowest possible heights at all times Risk of injury from falling objects. Identify and secure any objects



which might fall. Observe the minimum 3 metre exclusion zone around the Forklift. Ensure Forklift is equipped with Falling Object Protection System (FOPS).

↑ DANGER!

- Always ensure terrain is stable and able to support weight of the Forklift + load. Check intended path for obstructions and faults such as pot holes, plastic manhole covers and edges of loading docks.
- Take care when entering or exiting the Forklift. Always use three points of contact when climbing in or out.
- Do not leave Forklift unattended when running. Always ensure machine is in "Park" or "Neutral" and handbrake applied. Exhaust gases are poisonous. Never run the engine in confined places, especially when unloading shipping containers.
- Keep hands well clear of the mast mechanism. Never reach through the Forklift mast.
- Be aware of rear end swing and risk of rear of forklift striking objects.
- Diesel or LPG is highly flammable. Turn off the engine when refueling or changing LPG tanks or when machine not in use. No Smoking.
- Fatigue warning: Do not operate continously for long periods. Never operate this Forklift if you are under the influence of alcohol, drugs, medications or any na vour shi

PLANNING FOR SAFETY

A Hazard Identification Assessment & Control site plan, including a Pedestrian Management Plan must be in place before starting any work.

BEFORE USING THE FORKLIFT:

- > Specify the tasks and methods for the job
- > Ensure that this Forklift is the best machine for the job
- > Understand the capabilities of this machine and its load capacity chart.
- > Any specific site hazards that may affect the safe use of this machine.
- > Site Emergency procedures

You must conduct a pre-start inspection of the Forklift to ensure all safety features are working correctly.

PERSONAL PROTECTIVE EQUIPMENT





HIGH VISIBILITY CLOTHING

PROTECTIVE FOOTWEAR

HEAD PROTECTION MAY BE REQUIRED

HEARING PROTECTION May be required if noise exceeds 85dB.

SUN PROTECTION: Protective clothing and sunscreen may be required for extensive outdoor use.

REFUELLING/RECHARGING: Always wear the specified PPE when refuelling the forklift or replacing LPG bottles or recharging batteries.

WORK ZONE

Forklift must be made safe when not in use, to prevent use by untrained personnel.

-) Max speed outdoors: 15km/hr (jogging pace).
- Max speed indoors: 5km/hr (walking pace).

or whenever your

sight is obscured.

> Take care in wet conditions. slippery conditions

WORK SITE PRECAUTIONS

Before commencing work ensure you understand the site traffic management plan, emergency procedures, that you know the locations of the site First Aid Kit and Fire Extinguishers and you can call 111 in an emergency.

3 metre exclusion zone

Unless you are using a secured Stopping distances increase in and certified man cage Forklift must **NEVER** be used for lifting personnel. Check all overhead hazards. Ensure the mast clears overhead obstacles such as wiring or doors. BLIND SPOT Always drive backwards if the load obscures your view. If blind parking you MUST use a spotter. You must beep your horn at blind corners

Never approach closer than 3 metres

unless acknowledged by Forklift operator.

SLOW